



A Division of P.I. Engineering

1/14/2003

RailDriver Reinstallation in Windows 98

If everything works in Microsoft Train Simulator, but the Speed Display on the RailDriver shows three dashes, "---" this may indicate an error in the installation process. Please follow this procedure (your Windows 98 disk may be required):

1. Unplug the USB connection between the RailDriver and your PC.
2. Uninstall the RailDriver software from the "**Add/Remove Programs**" application in Windows Control Panel.
3. Insert the RailDriver Installation disk and run "**rdsetup**" to reinstall the software.
4. Shut the computer down (power off).
5. Plug the RailDriver USB connector back into your PC.
6. Power up the computer. When Windows starts, it should recognize new hardware.
7. Follow the onscreen instructions to install the new hardware.
8. If Windows asks for your **Windows 98 Installation Disk**, insert the disk and follow the instructions.
9. If Windows asks for the **Driver Installation Disk**, insert the RailDriver Installation Disk, and point Windows to the "**setup**" folder.
10. If Windows says it cannot find the driver, point it toward the "**system**" folder on your hard drive (normally **c:windows\system**).

Please contact our Technical Support Department if you require additional help. Technicians are available M-F 8am - 5pm E.S.T. Messages posted after hours will receive our earliest possible attention.

E-mail: tech@raildriver.com

Phone: (517) 655-5523